




Wireless connected device with Zigbee protocol from the ChoruSmart system that can be with Home Gateway for "CONNECTED SMART HOME" solutions, for residential and small offices, both for new builds and renovations. Zigbee technology is a secure and reliable technology in which data is encrypted and every node in the network ensures reachability across all devices (mesh network).

Contacte de ieșire	2,3 A 240 V ac (according to IEC 60669-2-1)	Sursă de alimentare	100 + 240 V ac - 50/60 Hz
Nr. module	1	Nr. canale în ieșire	1
Radio connections	Zigbee (IEEE 802.15.4)	Standard	2014/53/EU, 2011/65/EU + 2015/863, EN 60669-2-1, EN 60669-1, EN 301 489-1, EN 301 489-17, EN 300 328, EN IEC 63000
Temperatură de funcționare	-5 ÷ +45 °C	Relative humidity (non-condensative)	Max 93%
Power output Zigbee	10 dBm	Putere max disipabilă (W)	2
Terminale de cablare	Cu șuruburi	Capacitate strângere terminal cabluri flexibile (mm²)	Max. 1,5
Capacitate strângere terminal cabluri rigide (mm²)	Max. 1,5	Categorie	Axial roller shutter command connected
Nr. canale în intrare	2 (for local command replication or sending additional Zigbee commands)	Tensiune de intrare	Mains supply voltage
Clasă de protecție IP	IP20 (with button key)	LED colour	Albastru
Local control	Via 2 front push buttons (to complete with button key)	Power supply of EGO SMART plate	Da
Zigbee control extension if installed in an EGO SMART plate (SHIFT function)	Yes (2 Zigbee command activated with front push buttons)		

DIMENSIONAL



TECHNICAL SYMBOLOGY

IP

IP20 (with button key)

STANDARDS/APPROVALS



GEWISS S.p.A. Via A. Volta, 1
24069 Cenate Sotto - Bergamo - Italy
tel. +39 035 94 61 11 fax +39 035 94 69 09

www.gewiss.com
sat@gewiss.com
Last update 03/04/2023

Data, measures, designs and pictures are shown only as informative purposes, and could be changed without previous notice