

CorePro GLASS LED candles and lusters



CorePro LEDCandleND4.3-40W E14 840B35CLG

Featuring a classic heritage design, these filament LED candle combines the familiar shapes of classic incandescent bulbs with the benefits of long-lasting LED technology. The LED candle bulb, a very easy choice for people who are looking for a retrofit LED replacement, the LED candle provides 90% energy savings compared with conventional lamps. CorePro Glass LED bulbs provide excellent quality of light for stairway lighting. The LED candle bulb offers a lifetime of 15,000 hours to reduce maintenance costs.

Product data

| General Information | |
|--------------------------------------|--------------------|
| Lighting Technology | LED |
| Flux measurement reference | Sphere |
| Switching Cycle | 20,000 |
| Nominal lifetime | 15,000 hour(s) |
| Cap-Base | E14 [E14] |
| | |
| Light Technical | |
| Color Code | 840 [CCT of 4000K] |
| Luminous Flux | 470 lumen |
| Color Designation | Cool White (CW) |
| Correlated Color Temperature (Nom) | 4000 K |
| Luminous Efficacy (rated) (Nom) | 109.00 lm/W |
| Color Consistency | <6 |
| Color rendering index (CRI) | 80 |
| LLMF At End Of Nominal Lifetime (Nom | 70 % |
| Flickering value (PstLM) | 1 |

| Stroboscopic effect value (SVM) | 0.4 |
|---------------------------------|-------------|
| | |
| Operating and Electrical | |
| Line Frequency | 50 to 60 Hz |
| Input Frequency | 50 to 60 Hz |
| Power Consumption | 4.3 W |
| Lamp Current (Nom) | 40 mA |
| Wattage Equivalent | 40 W |
| Starting Time (Nom) | 0.5 s |
| Warm-up time to 60% light | 0.5 s |
| Power Factor (Fraction) | 0.48 |
| Voltage (Nom) | 220-240 V |
| | |
| Temperature | |
| T-Case Maximum (Nom) | 55 ℃ |
| | |


Datasheet, 2023, July 6 data subject to change

CorePro GLASS LED candles and lusters

| Controls and Dimming | |
|-------------------------------|--------------|
| Dimmable | No |
| | |
| Mechanical and Housing | |
| Bulb Finish | Clear |
| Bulb Shape | B35 [B 35mm] |
| | |
| Approval and Application | |
| Energy Efficiency Class | F |
| Energy Consumption kWh/1000 h | 5 kWh |
| EPREL Registration Number | 387417 |
| CE mark | Yes |
| EU RoHS compliant | Yes |
| · | |


| Product Data | | |
|---------------------------------|--------------------------------|--|
| Full product code | 871951434740300 | |
| Order product name | CorePro LEDCandleND4.3-40W E14 | |
| | 840B35CLG | |
| Order code | 929002024392 | |
| Numerator - Quantity Per Pack | 1 | |
| Numerator - Packs per outer box | 10 | |
| Material number (12NC) | 929002024392 | |
| Full product name | CorePro LEDCandleND4.3-40W E14 | |
| | 840B35CLG | |
| EAN/UPC - Case | 8719514347410 | |


Dimensional drawing



| Product | D | С |
|--|-------|-------|
| CorePro LEDCandleND4.3-40W E14 840B35CLG | 35 mm | 97 mm |

Photometric data






Spectral Power Distribution Colour - CorePro LEDCandleND4.3-40W E14 840B35CLG

Accent Lighting Spots - CorePro LEDCandleND4.3-40W E14 840B35CLG


CorePro GLASS LED candles and lusters


Photometric data



Light Distribution Diagram - CorePro LEDCandleND4.3-40W E14 840B35CLG

Lifetime





Life Expectancy Diagram - CorePro LEDCandleND4.3-40W E14 840B35CLG

Lumen Maintenance Diagram - CorePro LEDCandleND4.3-40W E14 840B35CLG



© 2023 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.