



Phase busbar, 2-phases, 10qmm, fork connector, 12SU

Part no. EVG-2PHAS/12MODUL
Catalog No. 215641

EL-Nummer (Norway) 1657153

Similar to illustration

Delivery program

| | | |
|----------------------------|--|--|
| Basic function | | Busbar |
| Basic function accessories | | Busbar for miniature circuit-breaker Busbar for residual-current circuit-breakers Busbar for combined residual-current/power circuit-breaker |
| Busbar type | | 2 phase |
| Product range | | EVG |

Technical data ETIM 7.0

| | | |
|--|-----------------|------|
| Low-voltage industrial components (EG000017) / Phase busbar (EC000215) | | |
| Electric engineering, automation, process control engineering / Low-voltage switch technology / Component for low-voltage switching technology / Phase busbar (ecl@ss10.0.1-27-37-13-06 [ACN992011]) | | |
| Number of phases | | 2 |
| Number of poles | | 2 |
| Suitable for number of devices | | 6 |
| Pitch dimensions | mm | 0 |
| Cross section | mm ² | 10 |
| Length | mm | 210 |
| Number of modular spacings | | 12 |
| Rated permanent current I _u | A | 63 |
| Type of electric connection | | Fork |
| Insulated | | Yes |
| Rated surge voltage | kV | 4 |
| Conditioned rated short-circuit current I _q | kA | 25 |
| Max. rated operation voltage U _e | V | 500 |
| Rated short-time withstand current I _{cw} | kA | 0 |
| Suitable for devices with N-busbar | | No |
| Suitable for devices with auxiliary switch | | No |