

Article

413.3267
 FLUSH-MOUNTING SOCKET 3P+N+E IP44 32A 6h

Picture



Master data

Minimum order	10 NR
Net Weight	0.224 KG
EAN code	8001636248028
INTRASTAT code	85366990

TechData

Syntetical description	FLUSH-MOUNTING SOCKET
Commercial series	OPTIMA Series
Protection degree	IP44/IP54
Flange	84X106MM
Rated current	32A
Poles	3P+N+E
Working frequency	50Hz
Working frequency	60Hz
Rated voltage	346-415V
Colour	RED
Hour position	6h

Approvals and Certifications



CE
 Declaration of conformity



I.M.Q. - ENEC 03
 European Norms Electrical Certification



CCC (China)
 China Compulsory Certification mark

Standards and Laws



EN 60309-1 (1999)
 [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements



EN 60309-2 (1999)
 [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations



EN 60309-1/A1 (2007)
 [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements



EN 60309-2/A1 (2007)
[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations

Packaging

Description	Carton
Quantity	50
EAN code	8001636696218
Gross weight	12.5 KG
Volume	77123.75 CCM
Dimensions	355x550x395 (MM)
Description	Box
Quantity	10
EAN code	8001636696201
Gross weight	2.5 KG
Volume	10120.855 CCM
Dimensions	223x313x145 (MM)

Annexed



Technical drawing [DWG]







Technical drawing [PDF]



Technical drawing [STP]

Articoli Collegati:

	570.0032	SURFACE MOUNTING BOX 32A IP67 STRAIGHT
	570.0132	SURFACE MOUNTING BOX 32A IP67 ANGLED
	570.M0032	SURFACE MOUN.STRAIGHT BOX FOR 32A OUTLET
	570.M0132	SURFACE MOUN. ANGLED BOX FOR 32A OUTLET