



Ledinaire floodlights gen3

BVP164 LED60/840 PSU 50W SWB CE

- - 840 neutral white - - - Symmetrical

This Ledinaire floodlights range contains a selection of popular off-the-shelf LED luminaires that comes with the Philips high quality levels at a competitive price. Reliable, energy-efficient and affordable – just what you need.

Product data

General information	
Lamp family code	-
Light source colour	840 neutral white
Light source replaceable	No
Number of gear units	1 unit
Driver/power unit/transformer	No [-]
Driver included	Yes
Optical cover/lens type	G [Glass]
Luminaire light beam spread	110° x 110°
Control interface	-
Connection	Flying leads/cables
Cable	Cable 1.0 m without plug (CIK)
Protection class IEC	Safety class I
Flammability mark	NO [-]
CE mark	Yes
ENEC mark	-
Warranty period	3 years
Optic type outdoor	Symmetrical
Constant light output	No
Number of products on MCB (16 A type B)	44
Photobiological risk	Photobiological risk group 1 @200mm to EN62778
Photobiological risk specification	0.2 m
EU RoHS compliant	Yes
Light source engine type	LED
Light technical	
Upward light output ratio	0
Standard tilt angle post-top	-
Standard tilt angle side entry	-
Operating and electrical	
Input Voltage	220 to 240 V
Input frequency	50 or 60 Hz
Initial CLO power consumption	- W
Average CLO power consumption	50 W
End CLO power consumption	- W
Inrush current	1.68 A

Ledinaire floodlights gen3

Inrush time	0.0082 ms
Power factor (min.)	0.95

Controls and dimming

Dimmable	No
----------	----

Mechanical and housing

Housing material	Aluminium die-cast
Reflector material	Polycarbonate
Optic material	Glass
Optical cover/lens material	Tempered glass
Fixation material	Steel
Mounting device	MBA [Mounting bracket adjustable]
Optical cover/lens shape	Flat
Optical cover/lens finish	Clear
Overall length	173 mm
Overall width	232 mm
Overall height	26.1 mm
Effective projected area	0.028 m²
Colour	Grey
Dimensions (height x width x depth)	26 x 232 x 173 mm

Approval and application

Ingress protection code	IP65 [Dust penetration-protected, jet-proof]
Mech. impact protection code	IK07 [2 J reinforced]
Surge protection (common/differential)	2/2 kV
Sustainability rating	-

Initial performance (IEC compliant)

Initial luminous flux (system flux)	6000 lm
Luminous flux tolerance	+/-10%

Initial LED luminaire efficacy	120 lm/W
Init. Corr. Colour Temperature	4000 K
Init. Colour rendering index	>80
Initial chromaticity	(0.380, 0.380) SDCM <5
Initial input power	50 W
Power consumption tolerance	+/-10%
Init. colour rendering index tolerance	+/-2

Over time performance (IEC compliant)

Control gear failure rate at median useful life	5 %
50,000 h	
Lumen maintenance at median useful life*	80
50,000 h	

Application conditions


Ambient temperature range	-25 to +40 °C
Performance ambient temperature Tq	25 °C
Maximum dimming level	Not applicable

Product data

Full product code	871951453353099
Order product name	BVP164 LED60/840 PSU 50W SWB CE
EAN/UPC – product	8719514533530
Order code	53353099
SAP numerator – quantity per pack	1
Numerator – packs per outer box	16
SAP material	911401854483
Net Weight (Piece)	0.850 kg



Dimensional drawing



BVP164 LED60/840 PSU 50W SWB CE

Ledinaire floodlights gen3

