



**Order description**  
PROTECTOR K 230 V AC white

**Order number**  
ER10018916

**EAN code**  
4015120018916



### Short description:

- Photoelectric smoke detector for **230 V operation** with in-built relay driver for the PROTECTOR K switching relay
- Safety through automatic self-test with fault display
- Extra safety through genuine electronic smoke chamber testing at the push of a button
- Protection against false alarm thanks to antistatic smoke chamber
- Back-up 9 V monobloc battery (included)
- With VdS approval (approval no.: G208089)

### Technical data:

Mains voltage	230 V AC, 50 Hz
Battery operation	Back-up 9 V block battery (included)
Approx. power consumption	0.4 W
Tested in accordance with	DIN EN 14604, VdS, TÜV
VdS number	G208089
CPD number	0786-CPD-20471
Signal volume	approx. 85 dB/3 m
Networkability	up to 30 detectors by wire
Suitable for radio transmission	no
Electronic smoke chamber test	at the push of a button
Automatic testing	approx. every 45 seconds with fault display
Installation type	ceiling mounting
Approx. measurements	Ø 106 mm, height 48 mm
Colour	white, similar to RAL 9010

### Accessories

- EM10425608 - Basket guard 180/90 white
- EM10425615 - Basket guard 165/70 white
- ER10018923 - PROTECTOR K switching relay white
- ER10018992 - PROTECTOR K surface-mounted box white