


Flush-mounting axial dimmer module. Two axial push-buttons on the front for switching the connected load ON and OFF (short press) or for regulating the brightness (long press). The device must be completed with one of the front buttons key available. The device has N°3 DIP-switches, located on the back of the device, for feature configuration.

Descriere	Dimmer Assiale	Sursă de alimentare	100 ÷ 240 V ac - 50/60 Hz
Nr. module	2	Nr. canale în intrare	2
Local control	Via 2 front push buttons (to complete with button key)	Auxiliary input channel voltage	100 ÷ 240 V ac - 50/60 Hz
Temperatură de stocare	-25 ÷ +70 °C	N. canali ingresso LED	-
Temperatură de funcționare	-5 ÷ +45 °C	Tensione canali ingressi LED	-
Relative humidity (non-condensative)	Max 93%	Nr. canale în ieșire	1
Front light signaling	Led albastru	Contacte de ieșire	-
Terminale de cablare	Cu șuruburi	240 V ac Incandescent-halogen lamps	4-150 W
Capacitate strângere terminal cabluri flexibile (mm²)	Max. 1,5	240 V ac LED lamps	4 ÷ 150W (max 5 lampade)
Capacitate strângere terminal cabluri rigide (mm²)	Max. 1,5	Loads piloted from electronic transformers 240 V ac	4 ÷ 150 VA (240 V ac)
Context	Interno, luoghi asciutti	240 V Fluorescent lamps	-
Clasă de protecție IP	IP20 (with button key)	Load control	Trailing edge
Standard	2014/35/EU (LVD), 2014/30/EU (EMC), 2011/65/EU + 2015/863 (RoHS), EN 60669-2-1, EN 60669-1, EN 300 328, EN IEC 63000		

DIMENSIONAL



TECHNICAL SYMBOLOGY

IP

IP20 (with button key)

STANDARDS/APPROVALS

UK CA **CE**

GEWISS S.p.A. Via A. Volta, 1
24069 Cenate Sotto - Bergamo - Italy
tel. +39 035 94 61 11 fax +39 035 94 69 09

www.gewiss.com
sat@gewiss.com
Last update 29/03/2023

Data, measures, designs and pictures are shown only as informative purposes, and could be changed without previous notice