




Flush-mounting axial roller shutter module. Device for commanding the motor that drives roller shutters, curtains, Venetian blinds, roller blinds, etc. via 2 interlocked output contacts with potential. Two axial push-buttons on the front for upward (UP) and downward (DOWN) movement, and for regulating the tilt of the slats.

The device must be completed with the front buttons key available.

The device has n°3 DIP-switches, located on the back of the device, for feature configuration.

Descriere	Comando motore assiale	Sursă de alimentare	100 ÷ 240 V ac - 50/60 Hz
Nr. module	1	Nr. canale în intrare	2
Local control	Via 2 front push buttons (to complete with button key)	Auxiliary input channel voltage	100 ÷ 240 V ac - 50/60 Hz
Temperatură de stocare	-25 ÷ +70 °C	N. canali ingresso LED	-
Temperatură de funcționare	-5 ÷ +45 °C	Tensione canali ingressi LED	-
Relative humidity (non-condensative)	Max 93%	Nr. canale în ieșire	2
Front light signaling	Led albastru	Contacte de ieșire	n. 2 x 2,3 A cosφ 0,6
Terminale de cablare	Cu șuruburi	240 V ac Incandescent-halogen lamps	-
Capacitate strângere terminal cabluri flexibile (mm ²)	Max. 1,5	240 V ac LED lamps	-
Capacitate strângere terminal cabluri rigide (mm ²)	Max. 1,5	Loads piloted from electronic transformers 240 V ac	-
Context	Interno, luoghi asciutti	240 V Fluorescent lamps	-
Clasă de protecție IP	IP20 (with button key)	Load control	-
Standard	2014/35/EU (LVD), 2014/30/EU (EMC), 2011/65/EU + 2015/863 (RoHS), EN 60669-2-1, EN 60669-1, EN IEC 63000		

DIMENSIONAL



TECHNICAL SYMBOLOGY

IP

IP20 (with button key)

STANDARDS/APPROVALS

