




Wireless connected device with Zigbee protocol from the ChoruSmart system that can be with Home Gateway for "CONNECTED SMART HOME" solutions, for residential and small offices, both for new builds and renovations. Zigbee technology is a secure and reliable technology in which data is encrypted and every node in the network ensures reachability across all devices (mesh network).

Culoare	Glossy white	Contacte de ieșire	1 NA / NC 5A (AC1) 240 V ac
Sursă de alimentare	100 ÷ 240 V ac - 50/60 Hz	Nr. module	2
Radio connections	Zigbee (IEEE 802.15.4)	Standard	2014/53/EU, 2011/65/EU + 2015/863, EN 60730-1, EN 60730-2-7, EN 60730-2-9, EN 301 489-1, EN 301 489-17, EN 300 328, EN IEC 63000
Temperatură de funcționare	-5 ÷ +45 °C	Relative humidity (non-condensative)	Max 93%
Power output Zigbee	10 dBm	Terminale de cablare	Cu șuruburi
Capacitate strângere terminal cabluri flexibile (mm²)	Max. 1,5	Capacitate strângere terminal cabluri rigide (mm²)	Max. 1,5
Categorie	Termostat	Clasă de protecție IP	IP20
Dimensiuni măsurate	Temperature, humidity	Funcții	Heating and cooling control; algorithms for 2-way systems: two-point (On/Off) and proportional integral (PWM).
Tip ecran	LCD		

DIMENSIONAL



TECHNICAL SYMBOLOGY

IP

IP20

STANDARDS/APPROVALS



GEWISS S.p.A. Via A. Volta, 1
24069 Cenate Sotto - Bergamo - Italy
tel. +39 035 94 61 11 fax +39 035 94 69 09

www.gewiss.com
sat@gewiss.com
Last update 29/03/2023

Data, measures, designs and pictures are shown only as informative purposes, and could be changed without previous notice