



Wireless connected device with Zigbee protocol from the ChoruSmart system that can be with Home Gateway for "CONNECTED SMART HOME" solutions, for residential and small offices, both for new builds and renovations. Zigbee technology is a secure and reliable technology in which data is encrypted and every node in the network ensures reachability across all devices (mesh network).

Culoare	Glossy white	Contacte de ieșire	1 NA 16 A (AC1) 240 V ac
Sursă de alimentare	100 ÷ 240 V ac - 50/60 Hz	Nr. module	1
Nr. canale în ieșire	1	Radio connections	Zigbee (IEEE 802.15.4)
Temperatură de funcționare	-5 ÷ +45 °C	Relative humidity (non-condensative)	Max 93%
Power output Zigbee	10 dBm	Terminale de cablare	Cu șuruburi
Capacitate strângere terminal cabluri flexibile (mm²)	Max. 2,5	Capacitate strângere terminal cabluri rigide (mm²)	Max. 2,5
Categorie	1-channel actuator with energy meter	Nr. canale în intrare	1 (for local command replication or sending additional Zigbee commands)
Tensiune de intrare	Mains supply voltage	Clasă de protecție IP	IP20
240 V ac Incandescent-halogen lamps	1920 W	240 V ac LED lamps	200 W
Loads piloted from electronic transformers 240 V ac	500 VA	LED colour	Albastru
Local control	Using front button	Power supply of EGO SMART plate	Da
Zigbee control extension if installed in an EGO SMART plate (SHIFT function)	Yes (1 Zigbee command)	Dimensiuni măsurate	Active power, energy consumed
Funcții	Timed load control, measures consumption, disconnection of load after exceeding threshold.		

## DIMENSIONAL



## TECHNICAL SYMBOLOGY

**IP**

IP20

## STANDARDS/APPROVALS



GEWISS S.p.A. Via A. Volta, 1  
24069 Cenate Sotto - Bergamo - Italy  
tel. +39 035 94 61 11 fax +39 035 94 69 09

www.gewiss.com  
sat@gewiss.com  
Last update 29/03/2023

Data, measures, designs and pictures are shown only as informative purposes, and could be changed without previous notice