




Wireless connected device with Zigbee protocol from the ChoruSmart system that can be with Home Gateway for "CONNECTED SMART HOME" solutions, for residential and small offices, both for new builds and renovations. Zigbee technology is a secure and reliable technology in which data is encrypted and every node in the network ensures reachability across all devices (mesh network).

Sursă de alimentare	100 ÷ 240 V ac - 50/60 Hz	Radio connections	Zigbee (IEEE 802.15.4)
Standard	2014/35/EU, 2014/30/EU, 2014/53/EU, 2011/65/EU, EN 62368-1, EN 303 446-1, EN 301 489-1, EN 301 489-17, EN 55032, EN 55035, EN 300 328, EN 62479	Temperatură de funcționare	-5 ÷ +45 °C
Relative humidity (non-condensative)	Max 93%	Power output Zigbee	10 dBm
Terminale de cablare	Cu șuruburi	Capacitate strângere terminal cabluri flexibile (mm²)	Max. 1,5
Capacitate strângere terminal cabluri rigide (mm²)	Max. 1,5	Categorie	EGO Smart plate power supply unit
Clasă de protecție IP	IP20	Power supply of EGO SMART plate	Da
Instalare	Recessed or with ChoruSmart supports with GW1x750 blanking module, inside the box of the EGO Smart plate to be powered		

DIMENSIONAL



TECHNICAL SYMBOLOGY

IP

IP20

STANDARDS/APPROVALS

