




Wireless connected device with Zigbee protocol from the ChoruSmart system that can be with Home Gateway for "CONNECTED SMART HOME" solutions, for residential and small offices, both for new builds and renovations. Zigbee technology is a secure and reliable technology in which data is encrypted and every node in the network ensures reachability across all devices (mesh network).

Sursă de alimentare	100 ÷ 240 V ac - 50/60 Hz	Dimensiuni LxHxP (mm)	40x40x20 mm
Measurement	Prin A.T.	Radio connections	Zigbee (IEEE 802.15.4)
Temperatură de funcționare	-5 ÷ +45 °C	Relative humidity (non-condensative)	Max 93%
Power output Zigbee	10 dBm	Terminale de cablare	Cu șuruburi
Capacitate strângere terminal cabluri flexibile (mm²)	Max. 1,5	Capacitate strângere terminal cabluri rigide (mm²)	Max. 1,5
Categorie	Energy meter with load control	Clasă de protecție IP	IP20
Instalare	Recessed in boxes and enclosures, on ChoruSmart supports using a GW1x750 blanking module, on DIN rails using GW16841 support plus a GW1x750 blanking module.	Dimensiuni măsurate	Active power, energy consumed
Funcții	Consumption meter, load control	Measured current	Max 70 A, min 0,05 A

DIMENSIONAL



TECHNICAL SYMBOLOGY

IP

IP20

STANDARDS/APPROVALS



GEWISS S.p.A. Via A. Volta, 1
24069 Cenate Sotto - Bergamo - Italy
tel. +39 035 94 61 11 fax +39 035 94 69 09

www.gewiss.com
sat@gewiss.com
Last update 04/04/2023

Data, measures, designs and pictures are shown only as informative purposes, and could be changed without previous notice