




Wirelessly connected device with Zigbee protocol from the ChoruSmart system. It can be used with Home Gateway for "CONNECTED SMART HOME" solutions and with Smart Gateway for "HOME AND BUILDING PRO" solutions. Ideal for residential and small commercial offices, new builds and renovations. Zigbee technology is a secure and reliable technology in which data is encrypted and every node within the network ensures reachability across all devices (mesh network). This device can also be used without Home Gateway and Smart Gateway (manual configuration with dip-switch or via IoT Configurator), in which case supervision via the app is not possible.

Categorie	Contacts interface	Protocol de comunicații	Zigbee (IEEE 802.15.4)
Tensiune de alimentare	Battery powered	Alimentare Baterii	CR2032 replaceable
Output power	8 dBm	Nr. canale în intrare	2
Tensiune de intrare	Potential-free	Lungime max cablu	15 m
Standard	2014/53/EU, EN 60669-2-1, EN 60669-1, ETSI EN 300-328	Clasă de protecție IP	IP20
Temperatură de funcționare	-5 ÷ +45 °C	Temperatură de stocare	-25 ÷ +70 °C
Relative humidity (non-condensative)	Max 93%	Dimensiuni LxHxP (mm)	42x40x20
Electrocod	051A		

DIMENSIONAL



TECHNICAL SYMBOLOGY

IP

IP20

STANDARDS/APPROVALS



GEWISS S.p.A. Via A. Volta, 1
24069 Cenate Sotto - Bergamo - Italy
tel. +39 035 94 61 11 fax +39 035 94 69 09

www.gewiss.com
sat@gewiss.com
Last update 08/09/2023

Data, measures, designs and pictures are shown
only as informative purposes,
and could be changed without previous notice