




Wirelessly connected device with Zigbee protocol from the ChoruSmart system. It can be used with Home Gateway for "CONNECTED SMART HOME" solutions and with Smart Gateway for "HOME AND BUILDING PRO" solutions. Ideal for residential and small commercial offices, new builds and renovations. Zigbee technology is a secure and reliable technology in which data is encrypted and every node within the network ensures reachability across all devices (mesh network). This device can also be used without Home Gateway and Smart Gateway (manual configuration with dip-switch or via IoT Configurator), in which case supervision via the app is not possible.

Categorie	Contacts interface	Protocol de comunicații	Zigbee (IEEE 802.15.4)
Tensiune de alimentare	230V ac - 50 Hz	Output power	8 dBm
Nr. canale în intrare	2	Tensiune de intrare	230V ac
Lungime max cablu	-	Standard	2014/53/EU, EN 60669-2-1, EN 60669-1, ETSI EN 300-328
Clasă de protecție IP	IP20	Temperatură de funcționare	-5 ÷ +45 °C
Temperatură de stocare	-25 ÷ +70 °C	Relative humidity (non-condensative)	Max 93%
Dimensiuni LxHxP (mm)	42x40x20	Electrocod	051A

DIMENSIONAL



TECHNICAL SYMBOLOGY

IP

IP20

STANDARDS/APPROVALS

