



EVGK busbar fork, 3-phase, L1 - L2 - L3, shortenable version with end caps included, 12 module units, 10 mm²



Part no. EVGK-3PHAS/12MODUL
EP-501069

General specifications

Product name	Eaton Moeller series busbar
Part no.	EVGK-3PHAS/12MODUL
EAN	9010653035138
Product Length/Depth	213 millimetre
Product height	28.5 millimetre
Product width	15 millimetre
Product weight	0.081 kilogram
Certifications	CE
Product Tradename	None
Product Type	Busbar
Product Sub Type	None
Countries	Mexico

Product Specification Details

Amperage rating	63 A
Color	Grey
Cross section	10 mm ²
EL number	1604096
Electric connection type	Fork
Features	Insulated Can be cut to size
Nominal current	63 A
Number of modular spacings	12
Number of phases	3
Number of poles	Three-pole
Pitch dimensions	17.8 mm
Rated conditional short-circuit current (I _q)	25 kA
Rated operating voltage (U _e) - max	415 V
Rated short-time withstand current (I _{cw})	0 kA
Rated surge voltage	4 kV
Rated uninterrupted current (I _u)	63 A
Suitable for	4 devices

Technical data ETIM 9.0

Low-voltage industrial components (EG000017) / Barra de fase (EC000215)			
Electric engineering, automation, process control engineering / Low-voltage switch technology / Component for low-voltage switching technology / Phase busbar (ecl@ss13-27-37-13-06 [ACN992016])			
Number of phases			3
Number of poles			3
Suitable for number of devices			4
Module width		mm	17.8
Cross section		mm ²	10
Length		mm	213
Can be cut to size			Yes
Width in number of modular spacings			12
Rated permanent current I _u		A	63
Type of electric connection			Fork
Insulated			Yes

Rated surge voltage		kV	4
Conditioned rated short-circuit current Iq		kA	25
Max. rated operation voltage Ue		V	415
Rated short-time withstand current Icw		kA	0
Suitable for devices with N-conductor			No
Suitable for devices with auxiliary switch			No
Colour			Grey