

632.4520-000

MODULAR ENCLOSURE
IP66 SURFACE MOUNTING BLOCK4
11 MOD. 212x415x105mm



* Product image may be indicative



EN 60670-1 (2005)
 EN 60670-24 (2013)

Low voltage direct. 2014/35/EU

■ GENERAL CHARACTERISTICS

Commercial Series	BLOCK Series
Synthetical description	MODULAR ENCLOSURE
Mounting version	SURFACE MOUNTING

■ TECHNICAL CHARACTERISTICS

Dissipable power	14W
------------------	-----

■ PHYSICAL CHARACTERISTICS

Material	THERMOPLASTIC
Mounting version	SURFACE MOUNTING
Protection degree IP	IP66
Protection degree IK	IK08

■ DIMENSIONAL CHARACTERISTICS

Modularity	BLOCK4
N.° modules	11 MOD.
Dimensions	212x415x105mm

■ DOWNLOAD

Technical drawing [PDF]
 Technical drawing [DWG]
 Technical drawing [STP]
 Instruction manual

■ OPTIONS & VARIOUS NOTES

Catalogue notes	50x60 mm cut-outs
	Power dissipation calculated in conformity with IEC EN 62208 and IEC EN 60670-24 standards
	70x87mm cut-outs
	With cut-outs to contain 16A (70x87mm) or, with suitable adaption, 32A socket (84x106mm) and DOMOPLUS Series in the grey coloured positions