

PHILIPS

Ledinaire Highbay

BY030P

Indoor

CE

UKA

D

GLOW WIRE 650°C

Max. 50°C Min. 0-20°C

LIFE 50K hrs @L80

220V 240V

50Hz 60Hz

Class I

IP65

IK07

Type Description	Power (W)	Voltage (V)	Frequency (Hz)	CCT (K)	D (mm)	H (mm)	Light source energy efficiency class
BY030P LED150_220_280S/840_50_65 PSU_WB	100W 145W 195W Selectable	220-240	50/60	4000K 5000K 6500K Selectable	320	119 2.39	D

Reflector (optional)

Reflector needs to be ordered separately

12NC	Description	d	h
911401812987	Highbay Reflector AL-L_Z	437	150

Hook Mounting

Watts	CCT
100W L	I 4000K
145W M	II 5000K
195W H	III 6500K

Cable connection

Blue Brown

23 24

1.5~2.5 N.m 1.5~2.5 N.m

22 6 15

Cable: 60245IEC57
Min. 3x1.0 mm²
Max. 3x2.5 mm²
Ø 6.5 - Ø 7.5 mm

0.8±0.1 Nm

Bracket Mounting (optional)

70

12NC	Description
911401813087	Highbay MB_Z

Bracket needs to be ordered separately

Max.M8:30N.m
Max.M4:6N.m

Optional: Reflector Mounting

1.5

Safety cable/chain mounting

These holes are for safety cable/chain